ET HANDHELD SERIES

FEATURES

1.8 GPM @ 1400 PSI or 3 GPM @ 1000 PSI; 2 HP



PRESSURE WASHERS / SINCE 1970

COLD WATER

_____р

DIRECT DRIVE

Model ET-301109D 25° high pressure Quick Connect Nozzle conveniently mounts to unit

Heavy-duty Hotsy Trigger Gun with chrome plated wand with side handle

50 ft. steel wire-braided **High Pressure hose** rated for up to 4000 PSI. With 24-inch Hose Guard and swivel fitting for tangle-free handling

ET SERIES

ELECTRIC

Thermal pump protector prevents excessive heat or pressure buildup for safety

The reliable **Hotsy Triplex pump** carries a 7-year limited warranty....best in the industry

Pressure-trapping unloader safety feature diverts water flow when trigger gun is not in use

Rubber pads absorb vibration for longlife and to keep the unit from moving or "walking" while in operation

Reliable industrial Motor with **1725 RPM**, reset button, capacitor start and full-service factor for longer life

36 ft. Electric Cord with NEC approved ground fault circuit interrupter for operator protection

Model ET-201409DX2

The **ET-201409DX2** features Auto Start-Stop, which allows the operator to start and stop the washer by pulling or releasing the trigger gun; this also provides additional protection for the high-pressure pump

••••••

25° high pressure Quick Connect Nozzle conveniently mounts to unit

Spring-loaded Trigger Gun with twopiece, twist-lock, easy grip Spray Wand 25 ft. steel wire-braided **High Pressure hose** rated for up to 3000 PSI. With 24-inch Hose Guard and swivel fitting for tangle-free handling

Remote wall switch with 10-foot electrical

in turning the washer on in wash bay installations



MODEL PART NO. GPM PSI ΗP VOLT/PH PUMP MODEL HOSE (FT) DIMENSIONS SHIP WT (LBS) ET-301109D 1.106-107.0 3.0 1000 2.0 115/1 HF2830S 50 20"x19"x17" 121 ET-201409DX2 1.107-089.0 18 1400 2.0 115/1 HFP2030S 25 20"x19"x17" 123

HOTSY.COM

NOTE: We are constantly improving and updating our products. Consequently, pictures, features & specifications in this brochure may differ slightly from current models. Flow rates & pressure ratings may vary due to variances allowed by manufacturers of our machine components. We meet the CETA testing specs for machine performance at $+_{10\%}$ and in some cases are tighter within $+_{-}$ 5% of listed specifications.

THE **BRAND** THE PROS USE

Specifications & product descriptions subject to change without notice. Hotsy's manufacturing facilities have established and apply a quality and environmental management system to be ISO 9001:2008 and ISO 14001:2001 certified.

© 2021 Kärcher North America P/N HOT_CWC Effective 06/21 Distributed by:

Hotsy Cleaning Equipment, Inc. 2732 Old Austin Peay Hwy. Memphis, TN 38128 (901) 379-0550 hotsyofmemphis@bellsouth.net